

Obudowy przemysłowe z ABS

Obudowy z ABS
Seria 300 i 3000
Kolor: ciemnopopielaty
Temperatura pracy: od -20°C do 80°C
Stopień ochrony: IP65
Klasa palności: UL94 HB

Śruby pokrywy: M4, stal nierdzewna
Uszczelka: neopren

G 302	64 x 58 x 35 mm
G 303	184 x 36 x 35 mm
G 304	115 x 65 x 40 mm
G 308	115 x 65 x 55 mm
G 311	115 x 90 x 55 mm
G 313	171 x 121 x 55 mm
G 317	222 x 146 x 55 mm
G 331	115 x 90 x 80 mm
G 340	171 x 121 x 80 mm
G 346	195 x 80 x 55 mm
G 353	222 x 146 x 75 mm
G 362	52 x 50 x 35 mm
G 366	82 x 80 x 55 mm
G 368	160 x 80 x 55 mm
G 369	160 x 80 x 85 mm
G 373	200 x 120 x 75 mm
G 378	265 x 185 x 95 mm
G 386	120 x 120 x 60 mm
G 387	120 x 120 x 90 mm
G 396	160 x 160 x 60 mm
G 399	160 x 160 x 90 mm
G 3008	240 x 160 x 90 mm
G 3019	240 x 160 x 120 mm
G 3028	300 x 230 x 86 mm
G 3031	300 x 230 x 111 mm
G 3039	360 x 200 x 150 mm
G 3101	100 x 100 x 55 mm
G 3103	100 x 100 x 90 mm
G 3107	120 x 80 x 55 mm
G 3109	120 x 80 x 85 mm
G 3113	200 x 120 x 90 mm
G 3118	240 x 120 x 60 mm
G 3121	240 x 120 x 100 mm
G 3122	200 x 150 x 55 mm
G 3125	190 x 190 x 55 mm
G 3127	200 x 150 x 75 mm
G 3130	353 x 140 x 121,5 mm